

## CT1000 - LOOP POWERED COMPACT CONDUCTIVITY TRANSMITTER





Competitively priced

Easy-to-use

4-20mA loop-powered

Adjustable zero and span

Fully encapsulated

The model CT-1000 (encapsulated miniature transmitter) is a 2-wire, 4-20mA blind conductivity transmitter featuring encapsulated construction, high performance and compact size.

Connect a conductivity cell of k=0.1 or 1.0 to it to then transform the output to a 4-20mA current proportional to the conductivity level. This output may be transmitted over 2 wires to a control location. The same 2 wires provide power to the transmitter. Any DC power supply from 12 to 36V DC may be used. There are two adjustments on the transmitter to standardize the conductivity output marked as "SPAN" and "ZERO". The output can be monitored with a loop-powered meter, a loop resistor or a multimeter during the standardization process.

Sensing Solutions for today and beyond



# CT1000 - LOOP POWERED COMPACT CONDUCTIVITY TRANSMITTER

### **Specifications**

Measuring Range	0-50uS/cm (k=0.1), 5-500uS (k=0.1), 0-5000uS (k=1.0) or enquire for custom ranges
Linearity	+/- 2% of span
Dimensions	1.5"(38mm) x 2.0"(51mm) x 1.0"(25mm)
Operating Temperature	-25 to 70 Degrees C
Temperature Compensation	0-50 Degrees C with 10K NTC (in electrode)
Temp Comp	(User specified temperature elements)
Output	4-20mA
Power Requirement	12-36V DC, 0-750 Ohm load resistor
Reverse Polarity Protection	Via Internal diode

#### **Ordering Information**

Part Number	Description
CT-1000	4-20mA loop-powered blind conductivity transmitter. Specify either 0-50uS(k=0.1) or 5-500uS (k=0.1) or 0-5000uS(k=1.0) range when ordering
971426	Graphite conductivity sensor k=0.1 for use with CT-1000 (0-50uS or 5-500uS range)
971084	Graphite conductivity sensor k=1.0 for use with CT-1000 (0-5000uS range)

#### **In-Line TEE Adapters**

FC50P	1/2" NPT adapter
FC75P	3/4" NPT adapter

#### **Calibration Solutions-Quarts**

TDS1000	1000ppm/1417uS
TDS1500	1500ppm/2060uS
TDS3000	3000ppm/3900uS
TDS5687	5687ppm/7000uS
TDS9523	9523ppm/10000uS
TDS15000	15000ppm/16630uS
TDS30000	30000ppm/30100uS



Tel: 714-895-4344 Fax: 714-894-4839 E-mail: info@sensorex.com www.sensorex.com Many other value solutions are available. Contact Sensorex for a complete listing.