

EC/TDS/Temp Pocket Tester VisionPlus EC330

Features

- Large display screen- displays conductivity/TDS and temperature at the same time.
- Dual range with selectable or auto-ranging options.
- 1 or 2 point calibration.
- Replaceable electrode module ensures extended usefulness.
- Battery life over 100 hours.
- Low battery indicator.
- IP67 waterproof housing.
- RoHS compliant.





Specification	S	
Range	Conductivity	0~1999uS/cm; 0~19.99mS/cm
	TDS	0~1000mg/L; 1.0~ 10.00g/L
	Temperature	0.0~99.5 / 32~212
Resolution	Conductivity	5uS; 0.05mS/cm
	TDS	5mg/L; 0.05g/L
	Temperature	0.5 /1
Accuracy	Conductivity	±1%FS
	TDS	±1%FS
	Temperature	±0.5 /±1
Temp Compensation		0.0 to 60.0
Calibration		1 or 2 point (1415uS at 0~1999uS/cm range; 12.90mS at 0~19.99mS/cm range)
Electrode Type / Cell Constant		Two wire conductivity cell / 1.0
ATC		Thermistor, $10K\Omega$, at 25 .
Display		LCD
Power		LR44 x 4 batteries.
Battery Life		>100 hours.
Auto Power Off		After 10 minutes of inactivity.
Case		IP-67 waterproof.
Weight / Dimensions (W x D x H)		105 grams (Including batteries) /19.3cm x 4.4cm x 2.5cm
Accessories		
330P		Conductivity / TDS electrode module.